X15
MAIN PROPULSION



GENERAL SPECIFICATIONS

Configuration	In-line, 6 cylinder, 4-stroke diesel	
Aspiration	Turbocharged / Aftercooled	
Displacement	14.9 L	912 in^3
Bore & Stroke	137 x 169 mm	5.39 x 6.65 in
Rotation	Counterclockwise facing flywheel	
Fuel System	Cummins XPI	

COMMERCIAL RATINGS

			FUEL CONSUMPTION		EMISSIONS		
kW	**BHP**	**RPM**	**Rated L/hr (Gal/hr)**	**ISO Avg L/hr (Gal/hr)**	**IMO**	**EPA**	**EU**
Continuous							
336	450	1800	90.0 (24.0)	61.3 (16.2)	2	3	—
336	450	1800	82.0 (21.7)	57.6 (15.2)	2	—	—
373	500	1800	97.8 (25.8)	67.2 (17.8)	2	3	—
373	500	1800	90.7 (24.0)	62.9 (16.6)	2	—	—
429	575	1800	109.1 (28.8)	78.1 (20.6)	2	3	—
447	600	1800	108.9 (28.8)	75.1 (19.8)	2	—	—
Heavy Duty							
469	630	2100	123.8 (32.7)	84.3 (22.3)	2	3	—

PRODUCT DIMENSIONS

Length	mm (in)	1712	(67)
Width	mm (in)	1067	(42)
Height	mm (in)	1234	(49)
Weight	kg (lb)	1724	(3800)

Dimensions may vary based on selected engine configuration.